

BO-FLEX 110 SY



PVC control cable, VDE registered and with steel wire braid, flexible cable for various applications, U0/U: 300/500V



Image for illustration only

Conductor:	Fine wire according to VDE 0295, class 5/IEC 60228 class 5
Insulation:	PVC, Cores twisted in layers,
Colour Code:	Black with white numbers acc. to VDE 0293-334
Inner Sheath:	PVC, grey
Screen:	Braid of galvanized steel wires , PVC, grey
Outer Sheath:	PVC, transparent
Cable Printing:	- standard
Technical Data & Standard References	Advantage Extra mechanical protection due to braided steel wire High electrical performance due to 4 kV test voltage
	Product features Flame-retardant according IEC 60332-1-2 Good chemical resistance
	Technical Data: Nominal Voltage: U0/U: 300/500 V Test Voltage: 4000 V Minimum bending radius: Occasional flexing: 20 x outer diameter Fixed installation: 6 x outer diameter Temperature range: Occasional flexing: -5°C to +70°C Fixed installation: -40°C to +80°C

TECHNICAL DATA AND PRODUCT FEATURES

	TEMPERATURE RANGE Occasional flexing: -5°C to +70°C Fixed installation: -40°C to +80°C
	WORKING VOLTAGE U0/U: 300/500 V
	TEST VOLTAGE 4000 V
	BENDING RADIUS Occasional flexing: 20 x outer diameter Fixed installation: 6 x outer diameter

Application: Plant engineering Industrial machinery Heating and air-conditioning systems Areas with high mechanical stress For fixed installation as well as occasional flexing at free, non-continuously recurring movement without tensile load