

BO-PROFIBUS DB FIX PVC

PROFI BUS CABLES FOR FIXED INSTALLATION




Image for illustration only

Conductor:	Solid bare copper 0,34 mm ² (AWG22) complying with CEI EN 60228
Insulation:	Foam skin PE
Colour Code:	Core colours: green and red
Screen:	Aluminium/polyester tape with tinned copper wire braid having coverage 85%
Outer Sheath:	PVC class 43 according to UL1581 and C22.2 n°210. Colour violet RAL 4001
Technical Data & Standard References	Product features: Flame retardant: Horizontal flame test per UL758, FT2 test acc. to CSA C.22.2 n°210 Halogen gas emission: ≤ 18% IEC 60754, CEI EN 50267-2 Industrial oil resistance: IEC 60811-404 Water resistance: IEC 60811-402
	Norm references / Approvals: Reference Standards: IEC 61158 EN 50170-2 DIN 19245 EIA RS485 DESINA Approved UL/CSA Approved: AWM Style 20601 300V/80°C.
Electrical & Mechanical Data	Operating temperature: Fixed application - 40 to 80 °C Minimum bending radius: Fixed application 8 x D Electrical and transmission properties at 20°C Max operating voltage: 300 V Test voltage: 1500 V Max DC conductor resistance: 54 Ω/km Capacitance core/core (nom): 29 pF/m Characteristic impedance: 150 Ω (±10%) 1÷20 MHz Propagation velocity (approx): 78% Attenuation: max 0,3 dB/100m at 9,6 kHz max 0,4 dB/100m at 38,4 kHz max 0,5 dB/100m at 200 kHz max 2,1 dB/100m at 4 MHz max 4,0 dB/100m at 16 MHz

	max 4,4 dB/100m at 20 MHz Min. insulation resistance: 5,0 GΩ x km Transfer impedance: 7 mΩ/m at 100 kHz 3 mΩ/m at 1 MHz 0,6 mΩ/m at 10 MHz 2 mΩ/m at 30 MHz 8 mΩ/m at 100 MHz
--	--

Application:

The PROFIBUS DP cable for fixed installation complies with European Standards EN 50170 and international Standards IEC 61158 61784. This cable is used in connection systems for serial communication networks like RS 485.

Botec P/N	assembly	outer diameter [mm ± 10%]	Cu mass [Kg/km]	cable mass [Kg/km]
	1x2x0,34 mm ² /AWG22	8,0	25	73,7