

BO-SOLAR H1Z2Z2-K

Cable for photovoltaic systems



Image for illustration only

Conductor:	Cross-linked single core cable acc. to DIN VDE 0283-618 / DIN EN 50618
Insulation:	Cross-linked compound
Colour Code:	see table
Wrapping:	Copper wire tinned, finely stranded acc. to DIN VDE 0295 Class 5 / IEC 60228 Class 5
Outer Sheath:	Cross-linked compound
Technical Data & Standard References	Product features: resistant to: • UV radiation • ozone • weathering effects • for outdoor use • halogen-free
	Norm references / Approvals: Reference Standards: halogen-free acc. to DIN VDE 0482-754-1 / DIN EN 60754-1 / IEC 60754-1 • flame-retardant acc. to DIN VDE 0482-332-1-2 / DIN EN 60332 1-2 / IEC 60332-1-2 • smoke density acc. to DIN VDE 0482-1034-1+2 / DIN EN 61034 1+2 / IEC 61034-1+2 • UV-resistant acc. to DIN VDE 0283-618 / DIN EN 50618 Appen dix E • ozone-resistant acc. to DIN VDE 0283-618 / DIN EN 50618 • weather-resistant acc. to DIN VDE 0283-618 / DIN EN 50618 Ap pendix E • DC Voltage resistance of the insulation acc. to DIN VDE 0283-618 / DIN EN 50618 Tab. 2
Electrical & Mechanical Data	Temperature range: fixed -40°C to +90°C Permissible operating temperature of the conductor: +120°C Nominal Voltage: AC U0/U 1000/1000 V DC U0/U 1500/1500 V Test Voltage: 6500 V Minimum Bending radius: fixed 5x Outer-Ø

Application:

SOLARFLEX®-X H1Z2Z2-K NTS is used for wiring solar modules. The maximum permissible DC voltage of the system in which the cable is installed must not exceed 1.8 kV. The cable is suitable for use in and on devices and systems with protective insulation (protection class II). Basic version H1Z2Z2-K according to DIN EN 50618 / TÜV.

No. cores x cross-sec. mm ²	AWG, approx.	Outer-Ø min - max mm	Cu factor per km	Weight kg/km, approx.	blue Part no.	red Part no.	black Part no.
1 x 4	12	5.9 – 6.6	38.4	85.0			
1 x 6	10	6.5 – 7.1	57.5	112.0			
1 x 10	8	7.6 – 8.4	96.0	158.0			