

BO TC CABLE TEMP105 PVC 2X0,20mm² Ripcord

PVC -30°C to +105°C

Image for illustration only

One pair of solid conductors. Cores HR PVC insulated. Pair laid flat and welded together in a 'ripcord' construction.

Type:

Conductor:	1X2X0,20mm ² /AWG24 (0,5mm solid)
Insulation:	Heat Resistant PVC
Colour Codes:	*see colour table below
Wrapping:	Laid Flat
Screen:	No
Outer Sheath:	Heat Resistant PVC
Overall diameter:	2x3mm
Cable Printing:	- standard
Technical Data & other References	The grade of PVC used on these cables is to BS7655:Part 4 Section 4.2 Type 5/UL Style 105°C rated (15,000 hours at 105°C) 'Ripcord' construction allows for easy separation of conductors
	Temperature range °C: -30 to +105
	Physical properties - Abrasion Resistance: Good - Moisture Resistance: Very Good - Typical Weight (Kg /100m): 1,0
	Notes: -

*

Colour Codes available (other colour codes available on request)	
IEC 60584-3	 KX  KCB  TX  JX  NX  RCA/SCA  EX
ANSI MC96.1	 KX  JX  TX  NX  EX  SX  RX

Application: Incorporates Heat Resistant (HR) PVC suitable for use in the temperature range -30°C to +105°C