

BO-ETHERNET CAT 6 FLEX PVC

PROFINET cables for dynamic installation in high performances chain




Image for illustration only

Conductor:	Stranded bare copper complying with CEI EN 60228
Insulation: Colour Code:	Foam skin PE white/blue - blue, white/orange - orange, white/green - green, white/brown - brown
Inner Sheath:	LSZH compound (only AWG23 type)
Screen:	Aluminium/polyester tape with tinned copper wire braid having coverage 85%.
Outer Sheath:	PVC class 43 according to UL1581 and C22.2 n°210. Colour green RAL 6018
Technical Data & Standard References	Product features: Flame retardant: Horizontal flame test per UL758, FT2 test acc. to CSA C.22.2 n°210 Halogen gas emission: ≤ 18% IEC 60754, CEI EN 50267-2 Industrial oil resistance: IEC 60811-404 Water resistance: IEC 60811-402
	Norm references / Approvals: Reference Standards: EN 50288 DESINA Approved UL/CSA Approved: AWM Style 20601 300V/80°C.
Electrical & Mechanical Data	Operating temperature: Fixed application -30 to 80 °C Dynamic installation -5 to 70 °C Minimum bending radius: Fixed application 8 x D Flexible installation 10 x D (only flexible cond) Electrical and transmission properties at 20°C Max operating voltage: 300 V Test voltage: 1500 V Max DC conductor resistance: 140 Ω/km (AWG26) 69,2 Ω/km (AWG23) Capacitance core/core (nom): 50 pF/m at 800 Hz Characteristic impedance: 100 Ω (±15%) 1 ÷ 100 MHz

100 Ω ($\pm 20\%$) 1 ÷ 250 MHz

Min. insulation resistance:

5,0 G Ω x km

Application:

The ETHERNET Cat.6 SF/UTP (250 MHz) cables comply with the EN 50288-5-2/-1 standard, meeting the requirements for GIGABIT ETHERNET, enabling data flow of up to 1000 Mbit/s. Detailed specifications are available upon request.

Botec P/N	assembly	outer diameter [mm $\pm$ 10%]	Cu mass [Kg/km]	cable mass [Kg/km]
	4x2xAWG26/7	6,4	28	52
	4x2xAWG23/7	8,7	47	81